§ 65.12

§65.12 Revision of flood insurance rate maps to reflect base flood elevations caused by proposed encroachments.

(a) When a community proposes to permit encroachments upon the flood plain when a regulatory floodway has not been adopted or to permit encroachments upon an adopted regulatory floodway which will cause base flood elevation increases in excess of those permitted under paragraphs (c)(10) or (d)(3) of §60.3 of this subchapter, the community shall apply to the Administrator for conditional approval of such action prior to permitting the encroachments to occur and shall submit the following as part of its application:

(1) A request for conditional approval of map change and the appropriate initial fee as specified by §72.3 of this subchapter or a request for exemption from fees as specified by §72.5 of this subchapter, whichever is appropriate;

- (2) An evaluation of alternatives which would not result in a base flood elevation increase above that permitted under paragraphs (c)(10) or (d)(3) of §60.3 of this subchapter demonstrating why these alternatives are not feasible:
- (3) Documentation of individual legal notice to all impacted property owners within and outside of the community, explaining the impact of the proposed action on their property.
- (4) Concurrence of the Chief Executive Officer of any other communities impacted by the proposed actions;
- (5) Certification that no structures are located in areas which would be impacted by the increased base flood elevation:
- (6) A request for revision of base flood elevation determination according to the provisions of §65.6 of this part;
- (7) A request for floodway revision in accordance with the provisions of §65.7 of this part;
- (b) Upon receipt of the Administrator's conditional approval of map change and prior to approving the proposed encroachments, a community shall provide evidence to the Administrator of the adoption of flood plain management ordinances incorporating the increased base flood elevations and/

or revised floodway reflecting the postproject condition.

(c) Upon completion of the proposed encroachments, a community shall provide as-built certifications in accordance with the provisions of §65.3 of this part. The Administrator will initiate a final map revision upon receipt of such certifications in accordance with part 67 of this subchapter.

[53 FR 16279, May 6, 1988]

§65.13 Mapping and map revisions for areas subject to alluvial fan flooding.

This section describes the procedures to be followed and the types of information FEMA needs to recognize on a NFIP map that a structural flood control measure provides protection from the base flood in an area subject to alluvial fan flooding. This information must be supplied to FEMA by the community or other party seeking recognition of such a flood control measure at the time a flood risk study or restudy is conducted, when a map revision under the provisions of part 65 of this subchapter is sought, and upon request by the Administrator during the review of previously recognized flood control measures. The FEMA review will be for the sole purpose of establishing appropriate risk zone determinations for NFIP maps and shall not constitute a determination by FEMA as to how the flood control measure will perform in a flood event.

- (a) The applicable provisions of §§65.2, 65.3, 65.4, 65.6, 65.8 and 65.10 shall also apply to FIRM revisions involving alluvial fan flooding.
- (b) The provisions of §65.5 regarding map revisions based on fill and the provisions of part 70 of this chapter shall not apply to FIRM revisions involving alluvial fan flooding. In general, elevations of a parcel of land or a structure by fill or other means, will not serve as a basis for removing areas subject to alluvial fan flooding from an area of special food hazards.
- (c) FEMA will credit on NFIP maps only major structural flood control measures whose design and construction are supported by sound engineering analyses which demonstrate that the measures will effectively eliminate alluvial fan flood hazards from the area

protected by such measures. The provided analyses must include, but are not necessarily limited to, the following:

- (1) Engineering analyses that quantify the discharges and volumes of water, debris, and sediment movement associated with the flood that has a one-percent probability of being exceeded in any year at the apex under current watershed conditions under potential adverse conditions (e.g., deforestation of the watershed by fire). The potential for debris flow and sediment movement must be assessed using an engineering method acceptable to FEMA. The assessment should consider the characteristics and availability of sediment in the drainage basin above the apex and on the alluvial fan.
- (2) Engineering analyses showing that the measures will accommodate the estimated peak discharges and volumes of water, debris, and sediment, as determined in accordance with paragraph (c)(1) of this section, and will withstand the associated hydrodynamic and hydrostatic forces.
- (3) Engineering analyses showing that the measures have been designed to withstand the potential erosion and scour associated with estimated discharges.
- (4) Engineering analyses or evidence showing that the measures will provide protection from hazards associated with the possible relocation of flow paths from other parts of the fan.
- (5) Engineering analyses that assess the effect of the project on flood hazards, including depth and velocity of floodwaters and scour and sediment deposition, on other areas of the fan.
- (6) Engineering analyses demonstrating that flooding from scources other than the fan apex, including local runoff, is either insignificant or has been accounted for in the design.
- (d) Coordination. FEMA will recognize measures that are adequately designed and constructed, provided that: evidence is submitted to show that the impact of the measures on flood hazards in all areas of the fan (including those not protected by the flood control measures), and the design and maintenance requirements of the measures, were reviewed and approved

by the impacted communities, and also by State and local agencies that have jurisdiction over flood control activities.

- (e) Operation and maintenance plans and criteria. The requirements for operation and maintenance of flood control measures on areas subject to alluvial fan flooding shall be those specified under §65.10, paragraphs (c) and (d), when applicable.
- (f) Certification requirements. Data submitted to support that a given flood control measure complies with the requirements set forth in paragraphs (c) (1) through (6) of this section must be certified by a registered professional engineer. Also, certified as-built plans of the flood control measures must be submitted. Certifications are subject to the definition given at §65.2.

(Approved by the Office of Management and Budget under control number 3067-0147)

[54 FR 33551, Aug. 15, 1989]

§65.14 Remapping of areas for which local flood protection systems no longer provide base flood protection

- (a) General. (1) This section describes the procedures to follow and the types of information FEMA requires to designate flood control restoration zones. A community may be eligible to apply for this zone designation if the Administrator determines that it is engaged in the process of restoring a flood protection system that was:
 - (i) Constructed using Federal funds;
- (ii) Recognized as providing base flood protection on the community's effective FIRM; and
- (iii) Decertified by a Federal agency responsible for flood protection design or construction.
- (2) Where the Administrator determines that a community is in the process of restoring its flood protection system to provide base flood protection, a FIRM will be prepared that designates the temporary flood hazard areas as a flood control restoration zone (Zone AR). Existing special flood hazard areas shown on the community's effective FIRM that are further inundated by Zone AR flooding shall be designated as a "dual" flood insurance rate zone, Zone AR/AE or AR/AH with Zone AR base flood elevations, and AE